

FEATURES

- Fully compatible with the ISO 11898 standard
- Thermally protected
- High CMTI: 100 kV/μs
- Transmit Data (TXD) dominant time-out function
- Bus fault protection of -40V to +40V
- Input levels compatible with 3.3 V and 5 V devices
- Low loop delay: 150ns (Typical) 210ns (Max)
- At least 110 nodes can be connected
- High speed (up to 1 MBaud)
- High system level EMC performance
- packages: DUB8 $V_{ISO}=2500\text{ V}_{RMS}$
SOPW16, $V_{ISO}=5000\text{ V}_{RMS}$

PRODUCT APPEARANCE




Provide green and environmentally friendly lead-free package

DESCRIPTION

SIT1050ISO is a capacitively isolated CAN transponder, which complies with the technical specifications of the ISO11898 standard. It contains multiple logic input and output buffers separated by silicon dioxide (SiO_2) insulation barriers. The device provides differential transmit capability to the bus and differential receive capability to the CAN controller.


PARAMETER	SYMBOL	CONDITION	MIN.	MAX.	UNIT
WB DUB8 Withstand isolation voltage	V_{ISO}		2500 typ		V_{RMS}
WB SOPW16 Withstand isolation voltage	V_{ISO}		5000 typ		V_{RMS}
Common-Mode Transients	CMTI		50	100	$\text{kV}/\mu\text{s}$
Supply voltage	V_{cc}		4.5	5.5	V
Maximum transmission rate	$1/t_{bit}$	Non-return to zero code	1		Mbaud
CANH/CANL input or output voltage	V_{can}		-40	+40	V
Bus differential voltage	V_{diff}		1.5	3.0	V
High-level input voltage	V_{IH}	TXD	2	5.25	V
Low-level input voltage	V_{IL}	TXD	0	0.8	V
High-level output current	I_{OH}	Driver	-70		mA

PARAMETER	SYMBOL	CONDITION	MIN.	MAX.	UNIT
High-level output current	I _{OH}	Receiver	-4		mA
Low-level output current	I _{OL}	Driver		70	mA
		Receiver		4	mA
Virtual junction temperature	T _j		-40	150	°C



Function diagram

PIN CONFIGURATION



PIN DESCRIPTION

DUB8 pin description

PIN	SYMBOL	DESCRIPTION
1	V _{CC1}	Power Supply for Logic Side, range 3.0V~5.5V.
2	RXD	Receive data output.
3	TXD	Transmit data input.
4	GND1	Ground 1, the ground reference for Isolator Logic Side.
5	GND2	Ground 2, the ground reference for Isolator Bus Side.
6	CANL	LOW-level CAN bus line.
7	CANH	HIGH-level CAN bus line.



PIN	SYMBOL	DESCRIPTION
8	V _{CC2}	Power supply for Bus Side, range 4.5V~5.5V.

SOPW16 pin description

PIN	SYMBOL	DESCRIPTION
1	VCC1	Power Supply for Logic Side, range 3.0V~5.5V.
2	GND1	Ground 1, the ground reference for Isolator Logic Side.
3	RXD	Receive data output.
4	NC	No Connection.
5	NC	No Connection.
6	TXD	Transmit data input.
7	GND1	Ground 1, the ground reference for Isolator Logic Side.
8	GND1	Ground 1, the ground reference for Isolator Logic Side.
9	GND2	Ground 2, the ground reference for Isolator Bus Side.
10	GND2	Ground 2, the ground reference for Isolator Bus Side.
11	NC	Not connect.
12	CANL	LOW-level CAN bus line.
13	CANH	HIGH-level CAN bus line.
14	NC	Not connect.
15	GND2	Ground 2, the ground reference for Isolator Bus Side.
16	V _{CC2}	Power supply for Bus Side, range 4.5V~5.5V.

LIMITING VALUES

PARAMETER	SYMBOL	VALUE	UNIT
Supply voltage	V _{CC1} , V _{CC2}	-0.5~+6.5	V
TXD voltage	TXD	-0.5~V _{CC1} +0.5	V
Voltage range at any bus terminal	CANL, CANH	-40~40	V
Transient voltage on pins CANH, CANL see Fig.7	V _{tr}	-200~+200	V
Storage temperature	T _{stg}	-40~150	°C
Virtual junction temperature	T _j	-40~150	°C
Welding temperature range		300	°C

The maximum limit parameters mean that exceeding these values may cause irreversible damage to the device. Under these conditions, it is not conducive to the normal operation of the device. The continuous operation of the device at the maximum allowable rating may affect the reliability of the device. The reference point for all voltages is ground.

DRIVER ELECTRICAL CHARACTERISTICS

PARAMETER	SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT
CANH dominant output voltage	V _{OHD}	VI=0V, RL=60Ω, Fig.1 , Fig.2	2.9	3.4	4.5	V
CANL dominant output voltage	V _{OLD}		0.8		1.5	V
Bus recessive output voltage	V _{OR}	VI=3V, RL=60Ω, Fig.1 , Fig.2	2	2.5	3	V
Bus dominant differential output voltage	V _{ODD}	VI=0V, RL=60Ω, Fig.1 , Fig.2	1.5		3	V
Bus recessive differential output voltage	V _{ODR}	VI=3V, Fig.1 , Fig.2	-0.012		0.012	V
		VI=3V, NO LOAD	-0.5		0.05	V
Transmitter dominant voltage symmetry	V _{dom(TX)sym}	V _{dom(TX)sym} =V _{CC} -V _{CANH} - V _{CANL}	-400		400	mV
Transmitter voltage symmetry	V _{TXsym}	V _{TXsym} =V _{CANH} + V _{CANL}	0.9V _{CC}		1.1V _{CC}	V



PARAMETER	SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT
Common-mode output voltage	V _{OC}	Fig.8	2	2.5	3	V
Peak-to-peak Common-mode output voltage	ΔV _{OC}			30		mV
Short-circuit output current	I _{OS}	CANH=-12V, CANL=open, Fig.11	-105	-72		mA
		CANH=12V, CANL=open, Fig.11		0.36	1	mA
		CANL=-12V, CANH=open, Fig.11	-1	0.5		mA
		CANL=12V, CANH=open, Fig.11		71	105	mA
Recessive output current	I _{O(R)}	-27V<CANH<32V 0<VCC<5.25V	-2.0		2.5	mA
Common-Mode Transients	CMTI	Fig.12	±50		±100	kV/μs

(V_{CC1}=V_{CC2}=5V±10%, Temp=T_{MIN}~T_{MAX}, typical in V_{CC1}=V_{CC2}=+5V, Temp=25°C.)

DRIVER SWITCHING CHARACTERISTICS

PARAMETER	SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT
Propagation delay time, low-to-high-level output	t _{PLH}	Fig.4	31	65	120	ns
Propagation delay time, low-to-high-level output	t _{PHL}		25	45	90	ns
Differential output signal rise time	tr			25		ns
Differential output signal fall time	tf			50		ns
Bus dominant time-out time	t _{dom}	Fig.10	300	450	700	μs

(V_{CC1}=V_{CC2}=5V±10%, Temp=T_{MIN}~T_{MAX}, typical in V_{CC1}=V_{CC2}=+5V, Temp=25°C.)

RECEIVER
ELECTRICAL

PARAMETER	SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT
Positive-going input threshold voltage	V_{IT+}	Fig.5		800	900	mV
Negative-going input threshold voltage	V_{IT-}		500	650		mV
Hysteresis voltage ($V_{IT+} - V_{IT-}$)	V_{HYS}		100	125		mV
High-level output voltage	V_{OH}	$IO=-2mA$, Fig.6	4	4.6		V
Low-level output voltage	V_{OL}	$IO=2mA$, Fig.6		0.2	0.4	V
Power-off bus input current	$I_{(OFF)}$	CANH or CANL=5V, Other pin=0V		165	250	μA
Input capacitance to ground, (CANH or CANL)	C_I			13		pF
Differential input capacitance	C_{ID}			5		pF
Input resistance, (CANH or CANL)	R_{IN}	TXD=3V	15	30	40	k Ω
Differential input resistance	R_{ID}		30		80	k Ω
Input resistance matching	$R_{I_{match}}$	CANH=CANL	-3%		3%	
The range of common-mode voltage	V_{COM}		-12		12	V

($V_{CC1}=V_{CC2}=5V \pm 10\%$, Temp= $T_{MIN} \sim T_{MAX}$, typical in $V_{CC1}=V_{CC2}=+5V$, Temp= $25^\circ C$.)

RECEIVER SWITCHING CHARACTERISTICS

PARAMETER	SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT
Propagation delay time, low-to-high-level output	t_{PLH}	Fig.6	60	100	130	ns



PARAMETER	SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT
Propagation delay time, low-to-high-level output	t _{PHL}		45	70	105	ns
RXD signal rise time	tr			8		ns
RXD signal fall time	tf			8		ns

(V_{CC1}=V_{CC2}=5V±10%, Temp=T_{MIN}~T_{MAX}, typical in V_{CC1}=V_{CC2}=+5V, Temp=25°C.)

DEVICE SWITCHING CHARACTERISTICS

PARAMETER	SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT
Loop delay1, driver input to receiver output, Recessive to Dominant	t _{d(LOOP1)}	Fig.9	112		210	ns
Loop delay 2, driver input to receiver output, Dominant to Recessive	t _{d(LOOP2)}		112		210	ns

(V_{CC1}=V_{CC2}=5V±10%, Temp=T_{MIN}~T_{MAX}, typical in V_{CC1}=V_{CC2}=+5V, Temp=25°C.)

LOGIC SIDE ELECTRICAL CHARACTERISTICS

PARAMETER	SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT
High level input voltage	V _{IH}	TXD pin	2			V
Low level input voltage	V _{IL}	TXD pin			0.8	V
High level input current	I _{IH}	TXD pin			10	μA
Low level input current	I _{IL}	TXD pin	-10			μA
Output Voltage High	V _{OH}	I _{OH} =-4mA, RXD pin	VDD1-0.4			V
Output Voltage Low	V _{OL}	I _{OL} =4mA, RXD pin			0.4	V
Input Capacitance	C _{IN}	TXD pin		2		pF



OVER TEMPERATURE PROTECTION

PARAMETER	SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT
Shutdown junction temperature	$T_{j(sd)}$			160		°C

SUPPLY CURRENT

PARAMETER	SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT
V _{CC1} Supply current	I _{CC1}	V _I =0V or V _{CC1} , V _{CC1} =3.3V		1.8	2.8	mA
		V _I =0V or V _{CC1} , V _{CC1} =5V		2.3	3.6	mA
V _{CC2} Supply current	I _{CC2}	V _I =0V LOAD=60Ω		50	70	mA
		V _I =VCC		6	10	mA

(V_{CC1}=V_{CC2}=5V±10%, Temp=T_{MIN}~T_{MAX}, typical in V_{CC1}=V_{CC2}=+5V, Temp=25°C.)

FUNCTION TABLE

Table1.CAN TRANSCEIVER TRUTH TABLE

DRIVER			RECEIVER			
INPUTS	OUTPUTS		BUS STATE	CANH- CANL	RXD	
TXD	CANH	CANL			BUS STATE	
L	H	L	Dominate	$V_{ID} \geq 0.9V$	L	Dominate
H	Z	Z	Recessive	$0.5V < V_{ID} < 0.9V$?	?
Open	Z	Z	Recessive	$V_{ID} \leq 0.5V$	H	Recessive
X	Z	Z	Recessive	Open	H	Recessive

(1) H=high level; L=low level; X=irrelevant.

Table 2. DRIVER FUNCTION TABLE




INPUTS	OUTPUTS		Bus State
TXD ⁽¹⁾	CANH ⁽¹⁾	CANL ⁽¹⁾	
L	H	L	Dominate
H	Z	Z	Recessive


(1) H=high level; L=low level; X=irrelevant; Z=high impedance.

Table 3. RECEIVER FUNCTION TABLE

$V_{ID} = \text{CANH-CANL}$	$V_{ID} = \text{CANH-CANL}$	Bus State	Bus State
Normal or Silent	$V_{ID} \geq 0.9V$	Dominant	Dominant
	$0.5 < V_{ID} < 0.9V$?	?
	$V_{ID} \leq 0.5V$	Recessive	Recessive
	Open ($V_{ID} \approx 0V$)	OPEN	Recessive

(1) H=high-level; L=low-level; ?=uncertain.

TEST CIRCUIT

Fig.1 Driver Voltage, Current, and Test Definition

Fig.2 Bus Logic State Voltage Definition

Fig.3 Driver Vod Test Circuit



- A. The input pulse is supplied by a generator having the following characteristics: PRR \leq 125 kHz, 50% duty, $t_r\leq$ 6 ns, $t_f\leq$ 6 ns, $Z_0=50\Omega$.
- B. C_L includes instrumentation and fixture capacitance within $\pm 20\%$

Fig.4 Driver Test Circuit and Waveform






Fig.5 Receiver Voltage and Current Definition



- A. The input pulse is supplied by a generator having the following characteristics: PRR \leq 125 kHz, 50% duty cycle, $t_r \leq 6$ ns, $t_f \leq 6$ ns, $Z_0 = 50\Omega$.
- B. C_L includes instrumentation and fixture capacitance within $\pm 20\%$.


Fig.6 Receiver Test Circuit and Waveform



NOTE: $C_L=100\text{pF}$ includes instrumentation and fixture capacitance with $\pm 20\%$;


All V_L input pulses are supplied by a generator having the following characteristics: $t_r \leq 6\text{ ns}$, $t_f \leq 6\text{ ns}$, Pulse Repetition Rate (PRR)=25kHz, 50% duty cycle.



Fig.7 t_{en} Test Circuit and Waveform



A. All V_I input pulses are from 0 V to V_{CC} and supplied by a generator having the following characteristics: t_r or $t_f \leq 6\text{ ns}$. Pulse Repetition Rate (PRR) = 125 kHz, 50% duty cycle.



Fig.8 Peak-to-Peak Common Mode Output Voltage Test and Waveform





NOTE: $C_L=100\text{pF}$ includes instrumentation and fixture capacitance within $\pm 20\%$.

Fig.9 t_{LOOP} Test Circuit and Waveform



- A. The input pulse is supplied by a generator having the following characteristics: $t_f \leq 6\text{ ns}$, $t_r \leq 6\text{ ns}$, $Z_O = 50\ \Omega$;
- B. C_L includes instrumentation and fixture capacitance with $\pm 20\%$

Fig.10 Dominant Time-Out Test Circuit and Waveform






Fig.11 Driver Short-Circuit Current Test Circuit and Waveform



ADDITIONAL DESCRIPTION

1 Sketch

SIT1050ISO is an interface chip with isolation function for CAN protocol controller and physical bus, and can be applied to the fields of in-vehicle, industrial control etc. It is primarily intended for high-speed applications, up to 1 MBaud, in passenger cars. The device provides differential transmit capability to the bus and differential receive capability to the CAN controller, and fully compatible with the ISO 11898 standard.

Provide wide body SOPW16 package, isolation withstand voltage 5000V_{RMS}.

Provide wide-body DUB8 package, isolation withstand voltage 2500V_{RMS}, Common-Mode Transients up to 100kV/μs.

2 Current protection

A current-limiting circuit protects the transmitter output stage from damage caused by accidental short-circuit to either positive or negative supply voltage, although power dissipation increases during this fault condition.

3 Over temperature protection

The output drivers are protected against over-temperature conditions. If the virtual junction temperature exceeds the shutdown junction temperature $T_{j(sd)}$, the output drivers will be disabled until the virtual junction temperature becomes lower than $T_{j(sd)}$ and TXD becomes recessive again. By including the TXD condition, the occurrence of output driver oscillation due to temperature drifts is avoided.

4 TXD dominant time-out function


A ‘TXD dominant time-out’ timer circuit prevents the bus lines from being driven to a permanent dominant state (blocking all network communication) if pin TXD is forced permanently LOW by a hardware and/or software application failure. The timer is triggered by a negative edge on pin TXD.

If the duration of the LOW level on pin TXD exceeds the internal timer value (t_{dom}), the transmitter is disabled, driving the bus lines into a recessive state. The timer is reset by a positive edge on pin TXD.


5 Operating mode

SIT1050ISO works in high-speed mode, which is the default working mode.


DUB8 DIMENSIONS



top view





front view




side view

SOPW16 DIMENSIONS



TAPE AND REEL INFORMATION


A0	Dimension designed to accommodate the component width
B0	Dimension designed to accommodate the component length
K0	Dimension designed to accommodate the component thickness
W	Overall width of the carrier tape
P1	Pitch between successive cavity centers




PIN1 is in quadrant 1

Package Type	Reel Diameter A (mm)	Tape width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)
DUB8	330 ± 2.0	$24.4^{+2.0}_{-0.0}$	11.00 ± 0.10	9.60 ± 0.10	4.40 ± 0.10	16.00	$24.00^{+0.3}_{-0.1}$
SOPW16	330 ± 2.0	$16.4^{+2.0}_{-0.0}$	10.75 ± 0.10	10.70 ± 0.10	2.80 ± 0.10	12.00 ± 0.10	16.00 ± 0.20

ORDERING INFORMATION

TYPE NUMBER	PACKAGE	PACKING
SIT1050ISODUB8	DUB8	Tape and reel
SIT1050ISODW	SOPW16	Tape and reel

DUB8 is packed with 800 pieces/disc in braided packaging. SOPW16 is packed with 1000 pieces/disc in braided packaging.

REFLOW SOLDERING


Parameter	Lead-free soldering conditions
Ave ramp up rate (T_L to T_p)	3°C/second max
Preheat time ts ($T_{smin}=150^\circ\text{C}$ to $T_{smax}=200^\circ\text{C}$)	60-120 seconds
Melting time t_L ($T_L=217^\circ\text{C}$)	60-150 seconds
Peak temp T_p	260-265°C
5°C below peak temperature t_p	30 seconds
Ave cooling rate (T_p to T_L)	6°C/second max
Normal temperature 25°C to peak temperature T_p time	8 minutes max

Important statement

SIT reserves the right to change the above-mentioned information without prior notice.



VERSION HISTORY

Version number	Data sheet status	Revision date
V1.0	Initial version.	March 2022
V1.1	Adjusted the format.	November 2020
V1.2	Updated the maximum value of low loop delay; Updated DUB8 schematic.	February 2021
V1.3	Added V_{IH} , V_{IL} , I_{OH} and I_{OL} ; Added “logical side electrical characteristics”; Deleted the information of SOPW8; Added “tape and reel information”; Updated ordering information; Added “reflow soldering”; Added “important statement”; Added “revision history”.	December 2022